

Solutions for better living

HAND HELD SHOWER HOUSING MODIFICATION SPECIFICATION FORM

/	
Person's Name:	
Assessor's Name:	
Application No.:	
(

Fax to (09) 620 1702 or email moh@accessable.co.nz

1.	A hand held shower <u>WITHOUT</u> lowered mixer is required for: Existing shower over	er bath	☐ Ex	isting Shower Box	(
2.	2. A hand held shower with lowered mixer is required for:						
	Existing shower over bath New Shower Over Bath (no shower in situ)	Exist	ing Shov	wer Box			
	The position of the hand held shower and handrail supplied in the scope of works has been discussed and	agreed w	ith the C	ontractor.			
An	additional handrail (s) is required with this modification, please specify (Please explain reasons in the applic	cation):					
	A window is present in the modified area. A new temperature reducing valve is reducing valve.	quired.			_		
Nui	mber of wet walls that need to be removed and replaced, or any other additional hardware features or issu	es requiri	ng chan	ge:			
3.	Where any other hand held shower modification is required (Please complete an application in p	orinciple v	vithout c	ı quote).	_		
Exi	sting hot water pressure is: kpa						
	An alternative mixer is required to manage a lower water pressure, please specify:						
Ple	e following existing items will need to be removed during construction, eg heated towel rail, shaving poi ase specify those compliant items that need to be re-fitted (the person understands electrical items will meet code):				_		
	1				-		
	3.				-		
	Where remedial issues have been identified, eg water pressure or plumbing, rotten walls or floo Notification of Remedial Works Form.	rs, please	comple	te and include a			
Vote							
	. A new 1500mm long hand held shower, slide rail and lowered mixer will be included. The curtain will be positioned within the shower area and of sufficient length (1800mm) to contact the inside of the bath.						
	The mixer and slide rail supplied with the modification is positioned above the horizontal handrail at approx. 1000mm above the floor. One handrail is supplied with the shower modification and is generally positioned horizontally under the slide rail & mixer or as specified by the EMS Assessor.						
	The EMS Assessor must liaise with the Contractor to confirm that the existing plumbing and hot water system has sufficient water pressure/flow, ie 35 kpa at the hot water tap. The Contractor can discuss if any suitable alternative mixer options are available which are compatible with the water pressure. If the plumbing system is not compatible with the proposed hand held shower/plumbing modifications, the Contractor, with the support of the EMS Assessor, is to ensure that the property owner is aware of this and that the cost of any remedial work will be the property owner's responsibility.						
	The provision of heating and ventilation is a standard home owner responsibility. The Contractor, with the support of the Assessor, is to ensure that the property owner is aware that where a heated towel rail, shaver point, extractor, heater or other electrical item needs to be removed to allow the modification to proceed, the cost to upgrade the item to comply with the building code is the home owners cost and responsibility. They can talk with the Contractor about installing new compliant items at their cost.						
Ad	ditional Notes / Fitting Instructions:						
	IS Assessor nature	Date _	/	/			
Coi	ntractor Signature	Date	/	1			