

Solutions for better living

HAND RAIL – INTERNAL & EXTERNAL HOUSING MODIFICATION SPECIFICATION

(`
Person's Name:	
Assessor's Name:	
Application No.:	
	,

Fax to (09) 620 1702 or email moh@accessable.co.nz

1.	Internal Stairs - as	cending					
Location		Wooden banister	Dowel	Lengt	h mm Alte	Alternative Height mm	
Left	side of stairs						
Right	t side of stairs						
Both sides							
Appro	oximate year home w	vas built:					
		n or material is required, plea nation where there is additional		ify details, suppli	er, make, model/cod	le (Please explain the	
ntern	al Handrails / Grat	orails				Alternative	
Loca	tion Alumini	um Stainless Steel	Powder Coated	Quantity	Length mm	height mm	
Bath							
Shov	ver						
Toile	t 🗌						
		gn or material is required, plea cation where there is additional		ary details, suppl	ier, make, modelycoc	te (rieuse expluiii tile	
2.	External Handrail	 Galvanised Steel – ascend 	ling the steps or path				
						Alternative	
Loca		Left Side	Right Side	Both	Length mm	height mm	
	Door						
	t Door						
Path	An alternative design	gn or material is required, plea		ify details, suppl	ier, make, model/cod	de (Please explain the	
		cation where there is additional		o Contractor			
		nandrail/grabrail (s) has been di ere the steps exit, if they end or	_		nd Plage complete	un application in	
	principle without a d		i arriveways, or stidled / Coll	mion patris of Idi	ia. Fieuse compiete t	п аррисацыі ІІІ	



Solutions for better living

	Person's Name:	
	Assessor's Name:	
	Application No.:	
١		

Additional Notes:
Notes about Rails:
• If the home is built after 1992 the provision of one handrail for (both internal and external) steps or stairs is home owner responsibility

- If the home is built after 1992 the provision of one handrail for (both internal and external) steps or stairs is home owner responsibility.
- Step/stair rise and tread must be safe for anyone regardless of disability, eg stair rise 180mm to 190mm +- tolerance 10mm; stair tread 280mm +- tolerance 10mm. Funding for handrails can be considered once remedial works have been completed, please use a Notification of Remedial Works Form to note any issues.
- Path gradient and surface must be safe for anyone regardless of disability, eg a minimum of hard-packed gravel or another such solid surface, level with the surrounding step. Funding for handrails can be considered once remedial works have been completed, please use a Notification of Remedial Works Form to note any issues.
- Standard hand rail height is 900 -1000mm; distance between the inner edge of the rail and the wall will be no less than 45mm; handrail will extend parallel to the ground at least 300mm beyond the top and bottom step, unless this encroaches on the person's path of travel or the rail obstructs a shared path or drive. In these cases the rail should end in line with the edge of the bottom step but have the end of the rail turned
- Funding for handrails on paths or steps can be provided only to one main accessible route between the home and where a vehicle can be parked.

EMS Assessor				
Signature	D	ate	/	/
Contractor Signature	D	ate	/	1