



Accessible List Adult Power Wheelchair Range

		REAR-WHEEL DRIVE		REAR-WHEEL DRIVE		REAR-WHEEL DRIVE		MID-WHEEL DRIVE		MID-WHEEL DRIVE		MID-WHEEL DRIVE					
Power Wheelchair Name		Karma KP25 2.0		Q100 RWD		Q200 RWD		Aviva RX		M1		Pride J623 2.0		Q500M			
Product Image <i>(Note: images are for reference only, check packages on aSAP for items included)</i>																	
Supplier Product link		https://alliedmedical.co.nz/collections/complex-powerchairs/products/karma-kp252-lightweight-folding-powerchair		https://medifab.com/nz/product/quickie-q100-r-powered-wheelchair/		https://medifab.com/nz/product/quickie-q200-r-powered-wheelchair/		https://www.invacare.co.nz/move/powered-mobility/powered-wheelchairs/aviva-rx		https://www.permobil.com/en-nz/products/power-wheelchairs/m1		https://alliedmedical.co.nz/collections/complex-powerchairs/products/jazzy-623-20		https://medifab.com/nz/product/quickie-q500m/			
Power Wheelchair Configuration Category		Minimal		Minimal		Minimal		Moderate, High		Minimal, Moderate		Moderate		Moderate, High			
DRIVE	Drive Wheels		12" Pneumatic		12" Pneumatic		14" Pneumatic		14" Solid		14" Flat Free or Pneumatic		14" Solid Foam Filled / 14" Pneumatic		13" Pneumatic		
	Castor Wheels		8" Solid		8" Solid		9" Solid		8" or 9" Solid		Front 8" Solid / Rear 8" Solid		Front 6" Solid / Rear 6" Solid		Front 7" Solid / Rear 7" Solid		
	Anti-Tip Wheels		N/A		2"		2"		Twin 4" Soild Rubber Bush		N/A		N/A		N/A		
	Maximum Speed		Up to 6.0 km/h		6 km/h		10 km/h		10 km/h or 12.5 km/h		8 km/h		Up to 9.6 km/h		10 km/h		
	Ground Clearance		2.3"		2.3"		2.3"		2.75"		3"		2.7" (battery tray)		3"		
	Turning Radius		25.6 - 39.4"		62"		67"		39"		20.5"		20.5"		21"		
	Max Rated Slope		10° / 17.6%		6°		8°		6°		10°		7.5° / 13.2%		8°		
	Seating System		Slung upholstery		Standard		Standard		Ultra Low Maxx		Permobil M1		TRU-Balance 3		Sedeo Lite / Sedeo Pro		
SEATING & POSITIONING	Seating Sizes	Non-Tilt		W: 14-20" D: 16-20"		W: 17" D: 16-22"		W: 17" D: 16-22"		W: 11-22" D 12-24"		W: 14", 16", 18", 20" or 22" D: 14-22"		W: 12-22" D: 12-22"		W: 15-22" D:16-22"	
		Power Tilt		N/A		N/A		N/A		W: 11-22" D 12-24"		W: 14", 16", 18", 20" or 22" D: 14-22"		W: 12-22" D: 12-22"		W: 15-22" D:16-22"	
		Power Tilt & Elevate		N/A		N/A		N/A		W: 11-22" D 12-24"		N/A		W: 12-22" D: 12-22"		W: 15-22" D:16-22"	
	Seat to Floor Heights	Non-Tilt		19"		17.5"		19"		16.5"-19"		16", 17" or 18"		16.5" - 18.5"		16"-19"	
		Power Tilt		N/A		N/A		N/A		16.5"-19"		16", 17" or 18"		17.5" - 19.5"		16.5"-19"	
		Power Tilt & Elevate		N/A		N/A		N/A		16.5"-19"		N/A		17.5" - 19.5"		17"-19"	
	Maximum Elevation		N/A		N/A		N/A		12"		N/A		12.0"		12"		
	Recline		N/A		N/A		N/A		Power 90° - 170° / Manual 60° - 170°		Manual 85° - 120°		N/A		Power 90° - 130° Optional Power 90 - 150		
Power Leg Elevate		No		N/A		N/A		Yes		Manual 85° - 180°		No		Yes Power Elevating & Articulating			
ELECTRONICS & BATTERY	Lights		No		No		No		Standard		Standard		Optional		Optional		
	Battery Size/Type		20Ah for 14" W 40Ah for 16-20" W		Group 24 (55Ah)		Group 24 (55Ah)		Group 24 (73Ah)		Group 34 (60Ah)		NF-22 (50Ah)		Group 24 (60Ah)		
	Electronics		VR2 Controller		VR2		VR2		Linx		R-net		VR2 Controller		R-Net		
	Battery Charger		6A Off-Board		8A Off-Board		8A Off-Board		8A Off-Board		Permobil VoltPro 10A Off-Board		8A Off-Board		8A Off-Board		
	Motor Packages		2-Pole		2-Pole Rear Wheel		2-Pole Rear Wheel		4-pole 10 and 12.5 km/h		2-Pole Mid-wheel		2-Pole Mid-wheel		4-Pole Mid-wheel		
DIMENSIONS AND WEIGHTS	Battery Weight		2x 17.5 kg		2x 15 kg		2x 15 kg		2x 25.4 kg		2x 18 kg		2x 17.2 kg		2x 21 kg		
	Base Weight <i>(batteries excl.)</i>		35 kg		64 kg		68 kg		57 kg		99 kg		63 kg		93 kg		
	Weight Capacity		135 kg		125 kg		136 kg		136 kg		136 kg		136 kg		136 kg		
	Overall Length		43"		39.7"		42.1"		39" without footrests		35.5"		35.5"		31.5"		
	Overall Width		Seat width +7"		21.2"		22.8"		22" Narrow / 24" Wide		24"		24.2"		24"		